



# Mejeriet

Delicious Dairy product turn milk into money.

**InventAgri, Italy**  
Our main supplier of Small-scale,  
but sophisticated Dairy equipment.  
[www.inventagri.com](http://www.inventagri.com)

## 11.00 Unseemly components for running a dairy.

A dairy has many "unseemly" components essential for day-to-day operations. These include electrical power, water supply, refrigeration or cold storage facilities, cleaning utilities such as brushes, sinks, chemicals, and wastewater infrastructure necessary for producing and processing dairy products.

Please pay attention to the importance of these utilities because they are crucial for ensuring that the dairy operates smoothly and that products have a high safety standard

Without these components, the dairy would not be able to function correctly and could experience disruptions or even stoppage of production.

Therefore, dairy producers and processors must invest in the necessary equipment and infrastructure to ensure these unseen utilities are in good working order and regularly maintained. It helps minimize the risk of breakdowns or disruptions and ensures that the dairy can operate efficiently and effectively.

### 11.01 - Technical data – Water purification

Qty	ID	Water purification	Price - €	Total - €
	<b>JCV-010</b>	<b>ANTI SCALE DEVICE - COMPACT MODEL WITH VOLUMETRIC VALVE</b> Resin volume: 10 lt. Cycle capacity: 60 °Fr/m3 Nominal flow capacity: 800 l/h Cycle salt consumption (per cycle): 2 Kg Power supply: 220V/50hz - 3W In/Out Connections: 3/4" Supplied with pre-filter		
	<b>JCV-015</b>	<b>ANTI SCALE DEVICE - COMPACT MODEL WITH VOLUMETRIC VALVE</b> Resin volume: 15 lt. Cycle capacity: 90 °Fr/m3 Nominal flow capacity: 900 l/h Cycle salt consumption (per cycle): 3 Kg Power supply: 220V/50hz - 3W In/Out Connections: 3/4" Supplied with pre-filter		
	<b>JCV-030</b>	<b>ANTI SCALE DEVICE - COMPACT MODEL WITH VOLUMETRIC VALVE</b> Resin volume: 30 lt. Cycle capacity: 180 °Fr/m3 Nominal flow capacity: 1900 l/h Cycle salt consumption (per cycle): 6 Kg Power supply: 220V/50hz - 3W In/Out Connections: 3/4" Supplied with pre-filter		



- JDV-050 ANTI SCALE DEVICE - DOUBLE BODY MODEL WITH VOLUMETRIC VALVE**  
Resin volume: 50 lt.  
Cycle capacity: 300 °Fr/m<sup>3</sup> Nominal flow capacity: 2100 l/h  
Cycle salt consumption (per cycle): 7,3 Kg Power supply: 220V/50hz  
In/Out Connections: 1" Supplied with pre-filter
- JDV-070 ANTI SCALE DEVICE - DOUBLE BODY MODEL WITH VOLUMETRIC VALVE**  
Resin volume: 70 lt.  
Cycle capacity: 420 °Fr/m<sup>3</sup> Nominal flow capacity: 2500 l/h  
Cycle salt consumption (per cycle): 11,3 Kg Power supply: 220V/50hz  
In/Out Connections: 1" Supplied with pre-filter
- PFAA-034 SELF-CLEANING FILTER WITH MANOMETERS**  
Body 3/4" IN/OUT + 90 micron filter included
- PFAA-010 SELF-CLEANING FILTER WITH MANOMETERS**  
Body 1" IN/OUT + 90 micron filter included
- PFA-034 FILTER FOR ANTI SCALE DEVICE**  
Body 3/4" IN/OUT + washable filter 50 micron included
- PFA-010 FILTER FOR ANTI SCALE DEVICE**  
Body 1" IN/OUT + washable filter 50 micron included
- PFAM-034 FILTER FOR ANTI SCALE DEVICE WITH 2 MANOMETERS**  
Body 3/4" IN/OUT + washable filter 50 micron included
- PFAM-010 FILTER FOR ANTI SCALE DEVICE WITH 2 MANOMETERS**  
Body 1" IN/OUT + washable filter 50 micron included
- PFAD-034 FILTER FOR ANTI SCALE DEVICE - DOUBLE**  
Body 3/4" IN/OUT + washable filter 50 micron + 25 micron included
- PFAD-010 FILTER FOR ANTI SCALE DEVICE - DOUBLE**  
Body 1" IN/OUT + washable filter 50 micron + 25 micron included
- CFA-090 90 um SPARE FILTER CARTRIDGE FOR PFAA-xxx**
- CF-050 50 um SPARE WASHABLE FILTER CARTRIDGE FOR PFAx-xxx**
- CF-025 25 um SPARE FILTER CARTRIDGE FOR PFAx-xxx**  
pack of 10 pcs.
- CF-010 10 um SPARE FILTER CARTRIDGE FOR PFAx-xxx**  
pack of 10 pcs.
- LUV-012 UV DEVICE WITH LCD ELECTRIC PANNEL**  
Max. flow rate: 1200 l/h Power: 30W Connections: 3/4" IN/OUT (preview 10 um filtering)
- LUV-028 UV DEVICE WITH LCD ELECTRIC PANNEL**  
Max. flow rate: 2800 l/h Power: 40W Connections: 1" IN/OUT (preview 10 um filtering)
- LUV-012/0 UV SPARE LAMP - 30 W**
- LUV-028/0 UV SPARE LAMP - 40 W**
- KDA-001 WATER HARDNESS TEST KIT**



**GPA-020 AUTOMATIC PRESSURE SYSTEM**

Composed of: self-priming pump, pressure switch, food membrane tank. Flow capacity: 55-10 Lt/min

Tank capacity: 20 Lt.

Pressure range: 1-4 bar (presetted at 2,8 bar) Power supply: Monophase 230V/50Hz - 0,75 KW

**GPA-040 AUTOMATIC PRESSURE SYSTEM**

Composed of: self-priming pump, pressure switch, food membrane tank. Flow capacity: 65-10 Lt/min

Tank capacity: 40 Lt.

Pressure range: 1-4 bar (presetted at 2,8 bar) Power supply: Monophase 230V/50Hz - 0,75 KW

**GPA-060 AUTOMATIC PRESSURE SYSTEM**

Composed of: self-priming pump, pressure switch, food membrane tank. Flow capacity: 150-20 Lt/min

Tank capacity: 60 Lt.

Pressure range: 1-4 bar (presetted at 2,8 bar)

**Power supply: 230V/50Hz - 1,5 KW**