

## InventAgri, Italy

Our main supplier of Small-scale, but sophisticated Dairy equipment. www.inventagri.com

## 12.03 Pressure and foam cleaning

Pressure and foam cleaning prevents the build-up of dirt, bacteria, and other contaminants in hard-to-reach areas, such as corners, drains, crevices, and uneven surfaces.

The foaming agent helps to loosen and remove dirt, bacteria, and other contaminants, making it easier to clean these areas.

The combination of pressure and foam cleaning needs an experienced operator to do it right. Pressure washing and foam cleaning can effectively clean various surfaces but harm equipment if not done correctly.

IP-110 MONOPHASE HOT WATER CLEANER

Hot water regulation up to 100 °C

with: internal tank for detergent and 10 mt hose tube

Pump: 1450 rpm Capacity: 11 lt./min

Pressure: 110 Bar (1600 psi)

Power Supply: 220V/1/50Hz - 2,2 KW (60Hz version:

+10%)

IP-150 THREE PHASE HOT WATER CLEANER

Hot water regulation up to 100 °C

with: internal tank for detergent and 10 mt hose tube

Pump: 1450 rpm Capacity: 13 lt./min

Pressure: 150 Bar (2200 psi)

Power Supply: 400V/3/50Hz - 3,7 KW (60Hz version:

+10%)